BCS TILLER TINE TYPES

BCS has used MANY different tiller tine types over the 40+ years they have been sold in North America. Here is a full list of all styles. SOME are interchangeable with each other, some are NOT. Lengths listed are approximate for NEW tines (of course worn tines will be shorter).

TELLING LEFT-HAND FROM RIGHT-HAND TINES

This is simple: When looking down at the tiller (from the operator position, standing behind the tiller), any tine that curves to the LEFT is a Left-Hand tine, any tine that curves to the RIGHT is a Right-Hand tine. (In the pictures of the different tine-types below, the LH tines will be on the left side of the picture.)

<u>TILLER BOLT-PATTERN STYLES:</u> BCS uses 2 different bolt-patterns for time mounting: <u>OVERLAPPING</u> and <u>INDIVIDUAL</u>. Here are pictures of each:



OVERLAPPING: Tines "stack" on top of each other, sharing common mounting bolts. 4 bolts per full set of 4 tines.



INDIVIDUAL: Tines bolt on individually, not sharing any mounting bolts. 8 bolts per full set of 4 tines.

IMPORTANT NOTE: "LONG" TINES CANNOT BE INSTALLED IN PLACE OF

<u>"SHORT" TINES!!!</u> If your tiller had "short" tines on it originally, the hood & depth-adjustment systems are made for short tines...Long tines will NOT fit!!!



SHORT UNIVERSAL TINES

Length: 6.5"

Thickness: 6mm

Bolt-hole spacing: 2.25"

Mounting style: Overlapping

Mounting bolt head size: 13mm



LONG UNIVERSAL TINES

Length: 7.5"

Thickness: 6mm

Bolt-hole spac-

ing: 2.25"

Mounting style: Overlapping

Mounting bolt head size: 13mm

Continued on next page...



SHORT WIDE TINES

Length: 4.5"

Thickness: 6mm

Bolt-hole spacing: 1.125"

ig: 1.125

Mounting style: Individual

Mounting bolt head size: 17mm



LONG WIDE TINES

Length: 5.25"

Thickness: 6mm

Bolt-hole spacing: 1.125"

Mounting style:

Individual

Mounting bolt head size: 17mm

Note: BCS also sells these as "18-inch 'Rental' Tines"



"RENTAL" TINES

Length: 5.25"

Thickness: 8mm

Bolt-hole spacing: 1.125"

Mounting style: Individual

Mounting bolt head size: 17mm



745 / 945 / 948 TINES (also fit 750 "superduty" tiller)

Length: 5.25"

Thickness: 8mm

Bolt-hole spacing: 1.875"

Mounting style: Individual

Mounting bolt head size: 19mm



750 "Standard tiller" TINES

Length: 6.25"

Thickness: 6mm

Bolt-hole spacing: 1.125"

Mounting style: Individual

Mounting bolt head size: 17mm

WHEN ARE TINES WORN OUT?

The picture below illustrates tine wear. When tines are NEW, they have a completely square / flat "end". As they wear, they get rounded off at the tip. WHEN THERE IS NO "FLAT" AREA LEFT AREA LEFT AT THE "END", THE TINES ARE WORN OUT, BECAUSE NOW AS THEY CONTINUE TO WEAR, THE OVERALL LENGTH GETS SHORTER.

